

Safety Step TD™

Detectable Warning Systems

**BONDS
TO ASPHALT &
CONCRETE**

INTRODUCES



DETECTABLE WARNING MATS

- **INSTALLS IN MINUTES**
- **FLEXIBLE CEMENT MAT**
- **MEETS ALL ADA REQUIREMENTS**
- **FINISHED LOW PROFILE EDGE**
- **BONDS TO ASPHALT & CONCRETE**



••• Safety Step TD •••™

••• Detectable Warning Systems •••



RAMP UP DETECTABLE WARNING MATS

GENERAL INFORMATION

DESCRIPTION:

Truncated-dome tactile warning pattern for pavement.

Use SSTD RAMP UP System where ADA, transit, or building codes require a tactile warning surface, such as transit boarding platforms, curb ramps, and hazardous vehicle areas. The system may be installed directly over concrete or asphalt.

PRODUCT ATTRIBUTES:

The system is a factory complete patterned mat consisting of adhesives and coatings to form an ADA-compliant, high contrast, breathable surface.

APPLICABLE STANDARDS:

ADA Accessibility Guidelines (ADAAG) Section 4.29.2

California Division of State Architects (DSA) IR112-2, IR 11B-3, IR 11B-4

SSTD RAMP UP MAT is a pre-molded tactile dome sheet composed of fiber-reinforced, polymer-modified cement and coated with an acrylic resin emulsion. Mats are 2MM thick with truncated domes being 0.9 in. diameter by 0.2 in. high.

Sizes: 3' x 4' , 3' x 5' , 2' x 4' , 2' x 5' .

Patterns: *Inline (Square) Pattern* - 1.67 in. on center each way.

Wide Inline (Square) Pattern - 2.35 in. on center each way.

Offset (Staggered) Pattern - 1.67 in. on center diagonally.

LIMITATIONS:

Do not apply in temperatures below 50 degrees Fahrenheit.

Protect both Ramp Up Mat and Adhesive from freezing.

Do not cut Ramp UP Mat into radius configuration. (use SSTD Standard mat for this)

SURFACE PREP AND INSTALLATION:

Please refer to SSTD RAMP UP installation guide, available for download via website at www.safetysteptd.com

WARRANTY:

Five Year limited warranty available.

866.723.3883

1725 HOWARD PLACE - REDLANDS, CA 92373

WWW.SAFETYSTEPTD.COM